



PATENT  
P55281

## IN THE CLAIMS

Please amend claims 1 through 8, and add new claims 9 and 10, as follows:

Sub El  
1 (amended). ~~A flat panel display apparatus for receiving display information~~  
including video data and synchronizing data from a host processing digital data in a  
serial digital communication, said display apparatus adapted for operation without  
need for any analog-to-digital converter (ADC) or phase-locked loop (PLL) circuit  
for signal conversion, said display apparatus comprising:

a receiver for reconstructing said display information;

a synchronizing signal generator for generating a synchronizing signal by  
extracting the synchronizing data from said reconstructed display  
information;

a digital-to-analog converter (DAC) for converting said video data to a  
corresponding analog video signal; and

an output terminal for externally transferring said synchronizing signal and  
analog video signal to an analog display apparatus.

Sub Cl  
2 (amended). ~~[A flat panel display as defined in] The display apparatus of~~  
claim 1, further comprising a video data converter for converting line and dot  
numbers of said video data so as to correspond to a prescribed display mode when  
said synchronizing data has a different characteristic from said prescribed display  
mode, and ~~said synchronizing signal generator generates said synchronizing signal~~

RECEIVED  
OCT 16 2000  
TC 2750 MAIL ROOM

6 ~~corresponding to said display mode.~~

Sub  
E2  
1 3 (amended). A digital data processing [device used in] system including a  
2 host computer for processing digital data and a flat panel display apparatus for  
3 displaying display information received from [a] said host computer [processing  
4 digital data], said system comprising:

5 a transmitter connected to said host to transfer digital display information as  
6 serial data;

7 a receiver for reconstructing said digital display information;

8 a synchronizing signal generator for generating a synchronizing signal by  
9 extracting synchronizing data from said reconstructed display  
10 information;

Q1  
cont  
11 a digital-to-analog converter (DAC) for converting video data to a  
12 corresponding analog video signal; and

13 an output terminal for externally transferring said synchronizing signal and  
14 said analog video signal to an analog display apparatus;[, said flat panel  
15 display including said receiver, synchronizing signal generator and  
16 output terminal]

17 wherein said flat panel display apparatus includes said receiver, said synchronizing  
18 signal generator, and said output terminal; and

19 wherein said flat panel display apparatus does not utilize any analog-to-digital  
20 \* converter (ADC) or phase-locked loop (PLL) circuit for signal conversion.

1 4 (amended). [A flat panel display as defined in] The display apparatus of  
2 claim 2, further comprising:

3 a liquid crystal display (LCD) driver for receiving data output from said video  
4 data converter; and

5 a [liquid crystal display (LCD)] LCD display panel for receiving an output  
6 from said LCD driver.

*a-1  
cancel*  
1 5 (amended). [A flat panel display as defined in] The display apparatus of  
2 claim 1, said analog display apparatus comprising:

*Sub  
B4*  
3 an amplifier for receiving said video signal from said DAC via said output  
4 terminal and amplifying said video signal;

5 a deflection signal generator for receiving said synchronizing signal output  
6 from said synchronizing signal generator via said output terminal and for  
7 generating deflection signals;

8 a high voltage generator for receiving an output from said deflection signal  
9 generator and generating a high voltage;

10 a cathode ray tube (CRT) display for receiving said amplified video signal  
11 from said amplifier and output signals from said deflection signal  
12 generator and a high voltage from said high voltage generator.

1 6 (amended). [A digital data processing device used in a flat panel display as

2 defined in] The system of claim 3, [further] said system comprising a video data  
3 converter for converting line and dot numbers of said video data [so as] to correspond  
4 to a prescribed display mode when said synchronizing data has a different  
5 characteristic from said prescribed display mode, and said synchronizing signal  
6 generator generates said synchronizing signal corresponding to said display mode.

2 7 (amended). [A digital data processing device used in a flat panel display as  
defined in] The system of claim 6, further comprising:

3 a liquid crystal display (LCD) driver for receiving data output from said video  
4 data converter; and

5 a [liquid crystal display (LCD)] LCD display panel for receiving an output  
6 from said LCD driver.

1 8 (amended). [A digital data processing device used in a flat panel display as  
2 defined in] The system of claim 3, said analog display apparatus comprising:

3 an amplifier for receiving said video signal from said DAC via said output  
4 terminal and amplifying said video signal;

5 a deflection signal generator for receiving said synchronizing signal output  
6 from aid synchronizing signal generator via said output terminal and for generating  
7 deflection signals;

8 a high voltage generator for receiving an output from said deflection signal  
9 generator and generating a high voltage;

10 a cathode ray tube (CRT) display for receiving said amplified video signal from  
11 said amplifier and output signals from said deflection signal generator and a high  
12 voltage from said high voltage generator.

1 --9. In a flat panel display apparatus comprising:  
2 a receiver means for reconstructing video display information including video  
3 synchronization data from a host; and  
4 a conversion means for converting said data to a corresponding video signal;  
5 *the improvement comprising:*  
6 a means for converting said data to a corresponding video signal without  
7 utilization of an analog-to-digital converter (ADC) or a phase-locked  
8 loop (PLL) circuit.

1 --10. In a method of processing display information containing video data and  
2 synchronizing data from a host processing digital data in a serial communication, said  
3 method comprising the steps of:

- 4 (1) reconstructing said display information to provide reconstructed display  
5 information;  
6 (2) generating a synchronizing signal by extracting the synchronizing data from  
7 said reconstructed display information;  
8 (3) converting said video data to a corresponding video signal; and  
9 (4) transferring said synchronizing signal and video signal to a display;

10     *the improvement comprising:* a step for converting said video data to a corresponding  
11             signal without utilizing an analog-to-digital converter (ADC) or phase-locked  
12             loop (PLL) circuit.

---